## **Exposee**Surface Retarder to Create Exposed Aggregate







Exposee is a spray-applied, concrete surface retarder used to produce horizontal decorative exposed aggregate finishes. Applied to fresh concrete, Exposee retards the setting of surface mortar, eliminating the need for sand blasting or acid washing.

Use Exposee to create decorative and functional driveways, sidewalks, patios or rough surfaces to improve mechanical bonds for keyway joints, waterproofing membranes and cementitious coatings.

Exposee is tinted green to insure uniform application for equal depth of retardation.

Coverage Rate: 100 sq. ft./gallon Depth of Penetration: 1/4 inch

**Dwell Time:** 4 - 24 hours. **VOC Content:** 0 grams/liter

Exposee is available in 5 gallon pails.



## **Competitor Cross-Reference**

<b>Euclid Chemical</b>	Low-VOC Sealers	ChemMasters
Diamond Clear 350 Super Diamond Clear 350 EverClear 350 Luster Seal 350 Rez Seal 350		Polyseal <sup>™</sup> A Polyseal <sup>™</sup> Plus A Crystal Clear A Polyseal <sup>™</sup> A Polyseal <sup>™</sup> EZ Spray Cure & Seal 25A Silencure <sup>™</sup> A Silencure <sup>™</sup> SRT
	Water Based Cure & Seal	
Eucocure VOX Diamond Clear VOX		Safe Cure® & Seal 309 Polyseal™ WB
Penetrating Sealers		
Baracade Silane 100 Chemstop WB HD		Aquanil™ Plus 100 Spall Guard™ WB10
Film Forming Sealers for Stamped Concrete		
		Traz <sup>™</sup> 25A S & D Concrete Sealer 400A





## ChemMasters, Inc.

300 Edwards Street, Madison, OH 44057

Phone: 440-428-2105 Toll-Free: 800-486-7866 Fax: 440-428-7091 www.chemmasters.net info@chemmasters.net