

SAFETY DATA SHEET

LUMBER MARKING PAINT (ALL COLORS)

September 11, 2019

SECTION 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : LUMBER MARKING PAINT (All Colors)
PRODUCT NUMBER :
RECOMMENDED USE : Lumber Marking Paint
APPLICATION METHOD : Brush, roller or spray
MANUFACTURER : ChemMaster Inc.
300 Edwards Street
Madison, OH 44057
EMERGENCY NUMBER : ChemTrec 800-424-9300
TECHNICAL PHONE NUMBER : 800-486-7866, 440-428-2105

SECTION 2 -- HAZARDS IDENTIFICATION

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture : Acute toxicity, Inhalation (Category 4)
Skin irritation (Category 3)
Specific target organ toxicity - single exposure (Category 3)
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 12.7%

GHS label elements :

Hazard pictograms



Signal Word : **Warning**

Hazard statements : Harmful if inhaled. Causes mild skin irritation. May cause respiratory irritation.

Precautionary statements

General

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not breathe vapor.

Response

: Get medical attention if you feel unwell IF exposed or concerned: Get medical attention.

Storage

: Store locked up

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.
Please refer to the SDS for additional information. Do not transfer contents to other containers for storage.

SECTION 2 -- HAZARDS IDENTIFICATION

Hazards not otherwise classified Not Known

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture	Mixture
Other means of identification	Not available.

CAS number/other identifiers

NAME	CAS#	% (W/W)
hydrous calcium magnesium silicate mineral mixture	14807-96-6	17-20
titanium dioxide	13463-67-7	3-6
1,2-ethanediol	107-21-1	1-3
2,2,4-trimethyl-1-3-pentanediol monoisobutyrate	25265-77-4	1-2
Calcined kaolin	92704-41-1	1-2
blend of silica & organic solids	NE	1-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4 - FIRST AID MEASURES**Description of necessary first aid measures**

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SECTION 4 - FIRST AID MEASURES

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	No known significant effects or critical hazards.
Inhalation	No known significant effects or critical hazards.
Skin contact	No known significant effects or critical hazards.
Ingestion	No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact	No known significant effects or critical hazards.
Inhalation	No known significant effects or critical hazards.
Skin contact	No known significant effects or critical hazards.
Ingestion	No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments No specific treatment

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

SECTION 5 - FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media None known.

Specific hazards arising from the chemical In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides

Special protective actions for fire-fighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 7 - HANDLING AND STORAGE

Precautions for safe handling

Protective Measures	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters Occupational exposure limits Occupational Exposure Limits

Ingredient name	Exposure limits
titanium dioxide	ACGIH TLV (United States, 4/2014).
	TWA - 10 mg/m ³
	OSHA PEL (United States, 2/2013).
	TWA - 10 mg/m ³ (vacated)
	TWA - 15 mg/m ³
hydrous calcium magnesium silicate mineral mixture	ACGIH TLV (United States, 4/2014).
	TWA: 2 mg/m ³ 8 hours.
calcined kaolin	ACGIH TLV (United States, 4/2014).
	TWA: 2 mg/m ³ 8 hours.
	OSHA PEL (United States, 2/2013).
	TWA: 5 mg/m ³ 8 hours
1,2-ethanediol	ACGIH TLV (United States, 4/2014).
	CEILING - 100mg/ m ³ .

Appropriate engineering If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene Measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields

Skin protection

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Flash Point	Closed cup: >100°C (>212°F)
Explosion limits	Not available
Color	Teal
Odor	Not available
pH	8.3 - 8.5
Boiling/condensation point	Not available
Melting/freezing point	Not available
Specific gravity	1.243
Density (lbs/gal)	10.35
Vapor pressure	Not available
Volatility	77.49% (v/v), 62.16% (w/w)
Evaporation rate	Slower than ether
Solubility	Completely soluble in the following materials: water
Coating V.O.C.	93.59 gms/liter
Partition coefficient: noctanol/water	Not available
% Solid. (w/w)	37.84%

SECTION 10 - STABILITY AND REACTIVITY

Reactivity	No specific test data related to reactivity available for this product or its ingredients
Chemical stability	The product is stable
Possibility of hazardous reactions	.. Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No specific data
Incompatible materials	No specific data
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 - TOXICOLOGICAL INFORMATION

Practical Experience

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Direct skin contact may cause irritation. Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Direct eye contact may cause irritation. Mild eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful: may cause lung damage if swallowed.

CARCINOGENICITY: No information.

Acute Toxicity Values

SECTION 11 - TOXICOLOGICAL INFORMATION

The acute effects of this product have not been tested. Data on individual components are tabulated below

Product/ingredient name	Result	Species	Dose	Exposure
1. titanium dioxide	LD50 Oral -	Rat	>10 g/kg	
2. 1,2,propanediol	LD50 Oral -	Rat	22,000 mg/kg	
	LD50 skin -	Rabbit	20,800 mg/kg	
3. hydrous calcium magnesium silicate mineral mixture	LD50 Oral -	Rat	Unknown	
4 1,2-ethanediol	LD50 Oral -	Rat	>300 -<=2000mg/kg	

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Defatting irritant

Prolonged or repeated contact can de-fat the skin and lead to irritation, cracking and/or dermatitis.

Target organs :

Contains material which causes damage to the following organs: eyes.
Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin, stomach.

Carcinogenicity**Classification****Carcinogenicity :**

Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure.

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	A4	2B	-
hydrous calcium magnesium silicate mineral mixture		1 - Group 1: Carcinogenic to humans (Quartz) 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Hydrous magnesium silicate)	Known to be human carcinogen (Quartz)

Carcinogen Classification code:

ACGIH: A1, A2, A3, A4, A5

IARC: 1, 2A, 2B, 3, 4

NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen

Not listed or regulated as a carcinogen: -

Teratogenicity : Not known

Specific target organ toxicity - single exposure (Globally Harmonized System)

Inhalation - May cause respiratory irritation. - Lungs

Specific target organ toxicity - repeated exposure (Globally Harmonized System)

no data available

SECTION 12 - ECOLOGICAL INFORMATION

Environmental effects : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 13400 µg/l Fresh water Acute LC50 >1000000 µg/l Marine water	Crustaceans - Paiaemonates pugio Fish - Pimephales promelas	48 hours 96 hours

SECTION 13 - DISPOSAL CONSIDERATIONS**Waste disposal**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

SECTION 14 - TRANSPORT INFORMATION

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	Special provisions Not Applicable	Special provisions Not Applicable	Special provisions Not Applicable	Special provisions Not Applicable	Emergency schedules (EmS) Not Applicable

SECTION 14 - TRANSPORT INFORMATION

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

Special precautions for user

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 14 - TRANSPORT INFORMATION

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not available..

SECTION 15 - REGULATORY INFORMATION

[Federal regulations](#)

[State regulations](#)

[California Prop. 65](#)

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

SECTION 16 - OTHER INFORMATION

[Hazardous Material Information System \(U.S.A.\)](#)

Health	2
Flammability	0
Physical hazards	0

Caution HMIS ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDS's under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Indicates information that has changed from previously issued version.

Date of previous issue:

Organization that prepared the SDS: ChemMasters Inc.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by ChemMasters Inc., and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.