



ChemMasters®

SPECIALTY CONSTRUCTION PRODUCTS

Coating Repair Solvent

Repair of Solvent-Based Acrylic Coatings And Equipment Cleaner

P R O D U C T D A T A

DESCRIPTION

Coating Repair Solvent is a hydrocarbon solvent used following to repair whitening, roller and spray patterns from over or misapplied solvent-based acrylic cures and sealers. Use to clean "cobwebbing" on roller covers during application, sprayers and equipment used to apply solvent-based acrylic products.

USES

- Repair whitening and uneven application of solvent-based cures & sealers — improve roller & spray marks
- Clean tools, equipment, solvent resistant sprayers used to apply solvent-based cures and sealers
- Removal of over spray from various solvent resistant surfaces
- Cleans SBR, styrene acrylate, acrylic or linseed oil resins

Packaging Product Number

5 gal (18.9L)	36 per pallet	F6502.05
1 gal (3.8L)	4 per case	F6502.04

TECHNICAL DATA

Test Data

Flash Point °F (°C)	111 (44)
Odor	Aromatic hydrocarbon
Specific Gravity	0.87

Coating Repair:

See corresponding Tech Tip repair instructions at www.chemmasters.net/Support2.php

Overspray Removal:

Use to clean overspray of solvent-based film forming acrylics from solvent resistant surfaces only. If the solvent resistance of a surface is unknown, test in a small inconspicuous area prior to use.

Spray **Coating Repair Solvent** over contaminated surface and allow to dwell for approximately ten minutes, or until acrylic overspray can be removed with a **Coating Repair Solvent** dampened cloth. Rinse surface thoroughly with clean water and allow to dry.

Tool/Equipment Cleaning:

Use to clean solvent resistant surfaces of jobsite equipment and spray equipment used for application of solvent-based acrylics. Solvent resistant parts such as spray tips may be immersed in **Coating Repair Solvent** to loosen and dissolve dried acrylics. Rinse thoroughly with clean solvent and allow to dry.

CLEANUP

If desired, use a citrus degreaser to remove any solvent film from equipment used to apply **Coating Repair Solvent**.

LIMITATIONS

- **Coating Repair Solvent** is not designed to remove epoxy coatings
- **Coating Repair Solvent** is not recommended for removal of wax based curing membranes.
- Use outdoors only

STORAGE

Store tightly sealed containers away from direct sunlight or sources of heat. **Coating Repair Solvent** will not freeze. Close container immediately after each use to avoid build up of moisture which may cause rusting of the container and discoloration of the material.

Precautions

Danger: Flammable Liquid and Vapor. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Precautionary Statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond the container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

For professional use only.
Keep away from children.



ChemMasters®

An American Owned & Operated Company

300 EDWARDS STREET • MADISON, OHIO 44057-3112 (440) 428-2105 • FAX (440) 428-7091 • ORDERLINE: (800) 486-7866 www.chemmasters.net

May 2022