



ChemMasters®

SPECIALTY CONSTRUCTION PRODUCTS

Liquid Stamp Release

Bubblegum Scented Release Agent
for Stamped Concrete Finishes

P R O D U C T D A T A

DESCRIPTION

Liquid Stamp Release is a clear, bubblegum scented liquid treatment that promotes clean release of texturing mats and stamps used to create stamped concrete finishes. When properly applied to the surface of concrete and texturing tools it's lubrication will prevent adhesion and ensure clean separation for maximum aesthetics, then evaporate leaving no film or residue.

USES

- Decorative release for stamped and textured concrete

ADVANTAGES

- Promotes clean positive release of texturing mats and tools from concrete surfaces
- Reduces stamping imperfections in concrete
- Clear formula
- Evaporates without leaving a film or residue
- Pleasant bubblegum scent

Application: **Liquid Stamp Release** is best applied with a pressurized hand-held sprayer at a rate of 150 to 250 ft²/gal (13.9 to 23.2 m²/L). Apply evenly and uniformly to both concrete surface and texturing mats leaving no pinholes or gaps. Do not allow to puddle. Best results are achieved when working in limited areas due to rapid evaporation.

CLEANUP

Clean tools and equipment immediately after use with solvent such as xylene or mineral spirits.

STORAGE

Store tightly sealed containers in cool dry area away from direct sunlight and sources of heat. Shelf life of properly stored material is one year from date of manufacture.

LIMITATIONS

- Do not use as a tilt up bond breaker.
- For use on freshly placed concrete to receive a textured or stamped decorative finish.
- Do not use as a finishing aid or work into concrete surface.
- Do not over apply. Excess release agent can cause defects, voids and bug holes.
- In cold weather, condition material to 50°F (10°C) prior to application.

Packaging / Part Number

5 gal (18.9L)	36 pails/pallet	F6008.05
55 gal (208L)	4 / pallet	F6008.55

TECHNICAL DATA

Release complies with Ozone Transport Commission standards for Volatile Organic Compounds (VOC) and Federal EPA Regulation 40 CFR Part 59.

Estimating Guide

ft²/gal (m²/L)

Varies by profile/texture	150 to 250 (13.9 to 23.2)
---------------------------	---------------------------

DIRECTIONS

Surface Preparation: Mats, skins, texturing tools and concrete surface must be clean and free of any dust, dirt, laitance, hardened concrete or residue.

Mixing: **Liquid Stamp Release** does not require mixing and should never be diluted. Slightly agitate before use.

**For professional use only.
Keep out of reach of children.**



ChemMasters®

An American Owned & Operated Company

300 EDWARDS STREET • MADISON, OHIO 44057-3112 (440) 428-2105 • FAX (440) 428-7091 • ORDERLINE: (800) 486-7866 www.chemmasters.net

July 2022