



# ChemMasters

SPECIALTY CONSTRUCTION PRODUCTS

## 1203 EMULSIFIABLE SOLVENT CLEANER

### P R O D U C T D A T A

#### DESCRIPTION

1203 Emulsifiable Solvent Cleaner is a heavy duty cleaner for concrete and masonry surfaces. It is specially formulated to dissolve grease, oil, tar, tire marks and solvent based curing compounds.

#### USES

- Horizontal or vertical, exterior or well ventilated interior concrete and masonry surfaces
- Removal of hydrocarbon based contaminants on sealed or unsealed surfaces
- Garages, driveways, vehicular repair facilities, machine shops, manufacturing plants, loading dock areas
- Removal of aged, solvent based curing compounds and sealers
- Cleans floors and walls of printing inks, packaging glues and solvent based tile or carpet adhesives

#### ADVANTAGES

- Quickly removes built up deposits of oil, grease, tar and tile adhesives
- Economical alternative to mechanical removal methods
- Softens and lifts old curing and sealing compounds for removal prior to recoating
- Penetrates and loosens hydrocarbon contaminants for economical cleaning and removal

#### PACKAGING

1203 Emulsifiable Solvent Cleaner is packaged in 5 U.S. gallon/18.7 Liter pails, shipped 36 per pallet shrink wrapped.

1201 Citrus Cleaner Degreaser or 1202 Heavy Duty Cleaner/Degreaser must be used to clean surfaces following treatment with 1203.

#### TECHNICAL DATA

- Meets the requirements of the U.S.D.A. for use in federally inspected meat and poultry plants, Classification K-1

Color	Light Amber
Fragrance	Aromatic hydrocarbon
Appearance	Thin Clear Liquid
Viscosity	Water thin
Specific Gravity	0.89
Oven Stability	Passes
Freeze/Thaw Stability	3 cycles

#### DIRECTIONS

**SURFACE PREPARATION:** Vacuum or sweep to remove any loose dirt, dust or debris. Use with adequate ventilation.

**UNSEALED SURFACES:** Do not dilute 1203 with either water or solvents. Apply 1203 with mop or sprinkling can and allow to dwell for 5 minutes to loosen contaminants. Scrub with stiff bristle or wire brush or broom. Do not allow 1203 to dry on floor. Add more material if required.

Dilute either 1201 Citrus Cleaner Degreaser or 1202 Heavy Duty Cleaner/Degreaser by volume 8:1 with clean water. Work 1201 or 1202 into surface treated with 1203 with brush or broom. Rinse twice with copious amounts of clean, potable water.

**SEALED SURFACES:** Use caution if using 1203 as a cleaner only, undiluted material will soften most sealers and curing compounds. Dilute 1:1 with water and scrub and rinse as stated above.

If removal of sealing membrane is desired, apply 1203 Emulsifiable Solvent Cleaner full strength and allow to dwell for full 5 minutes. Scrub area with 1201 or 1202 as directed above and rinse well two to three times. Some sealers may require additional application of 1203 and 1201 or 1202 for complete removal.



## ChemMasters

An American Owned & Operated Company  
300 EDWARDS STREET • MADISON, OHIO 44057-3112  
(440) 428-2105 • FAX (440) 428-7091 • ORDER LINE: (800) 486-7866

Revised 11/13/98

YEL-16

## **CLEANUP**

Rinse tools and equipment with xylene, xylol or mineral spirits.

## **LIMITATIONS**

- Care must be taken when using 1203 Emulsifiable Solvent Cleaner on sealed or coated surfaces. Product may soften and lift sealers
- Do not use on resilient tile or substrates other than concrete or masonry without applying a small test area. Product may soften or discolor other types of materials
- To remove dark tire marks from sealed or unsealed surfaces, use ChemMasters' SkidDaddle.

## **STORAGE**

Store pails in cool, dry area away from sunlight and sources of heat. Shelf life is one year from date of manufacture.

## **CAUTION**

Combustible liquid. Keep out of reach of children. Severe eye and skin irritant. Avoid contact with skin or eyes. Use with adequate ventilation, do not breathe vapors.

***This Product is Formulated and Labeled for Industrial and Commercial Use Only***

*FOR BEST RESULTS AND SAFEST USAGE, USER IS SPECIFICALLY DIRECTED TO CONSULT  
THE CURRENT MATERIAL SAFETY DATA SHEET AND PACKAGE LABEL FOR THIS PRODUCT*

*We warrant our products to meet our published specifications and to be free from defects in materials and workmanship to the acceptable quality levels defined in these specifications. If acceptable quality levels are not specified, the acceptable quality levels will be those normally supplied by us for the product. We make no guarantee of the results to be obtained from the use of our products. The determination as to the adaptability of any of our products to the specific needs of the Buyer is solely Buyer's prerogative and responsibility. We are glad to offer suggestions on the use of our products. Nevertheless, there are no warranties given except such expresses warranties offered in connection with the sale of a particular product. Our liability shall be limited to replacement of, or refund of an amount not to exceed the purchase price attributed to, the goods as to which such claim is made. Our selection of one of these alternatives shall be Buyer's exclusive remedy. IN NO CASE SHALL WE BE LIABLE FOR CONSEQUENTIAL OR SPECIAL DAMAGES, EVEN IF WE HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THE FOREGOING WARRANTIES ARE IN LIEU OF ALL OTHER WARRANTIES, GUARANTEES, CO-CONDITIONS AND REPRESENTATIONS, EITHER EXPRESSED OR IMPLIED, WHETHER ARISING UNDER ANY STATUTE, COMMON LAW, USAGE OR TRADE, COURSE OF DEALING OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.*