

Graffiti Eraser

Graffiti Removal Product

SPECIALTY CONSTRUCTION PRODUCTS

DESCRIPTION

Graffiti Eraser is a noncorrosive graffiti removal product, scrub, and rinse well. compound designed for easy application to Some forms of graffiti may require vigorous remove several forms of graffiti from multiple subbing action for removal. A stiff natural bristle surfaces but is most effective on surfaces treated brush is ideal for these cases. Rinse area well with *Graffiti Stopper*.

USES

or other graffiti or tag marks from:

- Painted surfaces
- Exterior concrete and masonry
- Polished or galvanized metals
- Traffic signs
- Rail cars
- Sound barriers
- **Bridges**
- **Bathrooms**
- Schools or other areas subject to attack by graffiti artists

ADVANTAGES

- **Easy Application**
- Easy to use
- Highly effective on even the most difficult applications
- Available in five gallon pails

DIRECTIONS

Painted or polished metal substrates:

Apply Graffiti Eraser liberally to the contaminated surface by spray, brush, or roller. Allow Graffiti Eraser to work on the surface for at least 30 seconds up to 2 minutes. Graffiti Eraser may cause damage to normal paints and metal polishes if it remains on the surface for more than 2 minutes. Surfaces treated with Graffiti Stopper will not be effected by Graffiti Eraser. If Graffiti

Eraser should dry on the surface apply more

with clean water and repeat application if necessary.

For use on Masonry, brick, natural stone, plain Removes unwanted paint, crayon, magic marker, concrete, or surfaces coated with Graffiti Stopper:

> Apply Graffiti Eraser liberally. Spray application is preferred since this is the best way for it to penetrate the pores of the substrate. Allow Graffiti Eraser to penetrate the surface for 2 minutes but do not allow Graffiti Eraser to dry. If Graffiti Eraser dries on the surface, repeat application. On porous surfaces, stubborn forms of graffiti it may require scrubbing with a stiff nylon or natural brush—repeat as necessary. with clean water using moderate to high water pressure.

Limitations:

Do not apply to asphalt surfaces.

If painted surfaces are not coated with Graffiti Stopper, shadowing may appear.

Cautions:

Combustible Liquid: Keep away from heat or open flame. Use with adequate ventilation. May cause skin, eye, and respiratory tract irritation. Do not take internally. Keep out of the reach of children.

Storage:

Store in well ventilated area at room temperature 40°F to 71°F (5°C to 21°C). Do not freeze or heat containers. Shelf life of properly stored material is 2 vears.



This Product is Formulated and Labeled for Industrial and Commercial Use Only	
FOR BEST RESULTS AND SAFEST USAGE, USER IS SPECIFICALLY DIRECTED TO CONSULT THE CURRENT PRODUCT & SAFETY DATA SHEETS AND PACKAGE LABEL FOR THIS PR fe warrant our products to meet our published specifications and to be free from defects in materials and workmanship to the acceptable quality levels defined in these specifications. If acceptable, the acceptable quality levels will be those normally supplied by us for the product. We make no guarantee of the results to be obtained from the use of our be determination as to the adaptability of any of our products to the specific needs of the Buyer is solely Buyer's prerogative and responsibility. We are glad to offer suggestions on the use of our coducts. Nevertheless, there are no warranties given except such expresses warranties offered in connection with the sale of a particular product. Our liability shall be limited to replacem fund of an amount not to exceed the purchase price attributed to, the goods as to which such claim is made. Our selection of one of these alternatives shall be Buyer's exclusive remed ASE SHALL WE BE LIABLE FOR CONSEQUENTIAL OR SPECIAL DAMAGES, EVEN IF WE HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THE FOREGOING WE ES ARE IN LIEU OF ALL OTHER WARRANTIES, GUARANTEES, CO-CONDITIONS AND REPRESENTATIONS, EITHER EXPRESSED OR IMPLIED, WHETHER ARISING UNDER ANY S' ODMMON LAW, USAGE OR TRADE, COURSE OF DEALING OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNES ARTICULAR PURPOSE.	cceptable products. se of our ent of, or ly. IN NO /ARRAN- TATUTE,

©2001ChemMasters

Printed in U.S.A.