



February 14, 2013

To Whom It May Concern:

Safe-Cure® & Seal 309 is a single component, water-based, acrylic emulsion membrane-forming curing and sealing compound. This material meets the requirements of ASTM C-309 Type 1, Class B, AASHTO M-148 for concrete curing Compound.

The VOC content of this product is <100 g/L when calculated to California Air Resources Board Architectural Coatings Program. **Safe-Cure & Seal 309** meets the requirements of the South Coast Air Management District of less than 100 gm/L VOC for concrete curing compounds. This could qualify for EQ credit 4.1 Low Emitting Materials: Adhesives & Sealants, or 4.2 Low Emitting Materials: Paints and Coatings, but not both. This may also qualify for low emitting interiors.

There are no recycled materials used to manufacture **Safe-Cure & Seal 309**.

Safe-Cure & Seal 309 is manufactured at 300 Edwards Street, Madison, OH. 44057. If your project falls within a 500-mile radius or $(\text{Distance by rail}/3) + (\text{Distance by inland waterway}/2) + (\text{Distance by sea}/15) + (\text{Distance by all other means}) \leq 500$ miles [800 kilometers] the product is considered a locally produced material and can help contribute to earning MR Credit 5.1: Regional Materials: 10% Extracted, Processed & Manufactured Regionally 1 Point, and MR Credit 5.2: Regional Materials: 20% Extracted, Processed & Manufactured Regionally 1 Point in addition to MR Credit 5.1.

ChemMasters products by virtue of being manufactured in United States are in compliance with the "Buy American Provision" set forth in the American recovery Reinvestment Act (ARRA) of 2009, section 1605.

John Kirk
ChemMasters Technical Service Manager
PH (440) 428-2105
PH (800) 486-7866
FAX (440) 428-7091
johnkirk@chemmasters.net
www.chemmasters.net

300 Edwards Street, Madison, Ohio 44057-3112

Phone: (440) 428-2105 • (800) 486-7866 • Fax: (440) 428-7091

